



960 SERIES HD LIFT-LID COMBO DESK

When others are long gone this very well made in the USA product from USACapitol will still be vibrant and structurally sound in every way. Built better to last longer. Enjoy the peace-of-mind that comes with products designed for educational use.

H I G H L I G H T E S

- Premium Quality
- Lifetime Frame Warranty
- Minimum 3-1/2 feet of weld
- 2 Seat Heights
- 16 Gauge Legs
- 8 Seat/Back Colors
- 16 Gauge Back-Support
- Patented Glide System

Legacy™ 960 Series Lift-Lid Combination Desk Specifications

Frame: All-tubular design, 1-1/4" diameter, 16-gauge leg supports. 1", 16-gauge side brace is 360-degree arc-welded to both front and rear leg support and top support. A 1", 16-gauge back support is multiple arc-welded to the leg and top support. A 1-1/4", 16-gauge top support is arc-welded integrally with all tube parts for maximum structural integrity. Minimum 3-1/2 feet of total weld. Frame is chrome plated after all welding is complete. The frame shall be contoured to conform to the shape of the seat-back to accept uniform attachments.

Standard Chrome Finish: Chrome is comprised of metal layers (Nickel & Chromium) electrostatically bonded to metal. Our standard is 4-6 mills (25%-50% more than our competitors) of Nickel. Hard-Chrome will not scratch. CASS test per ASTM B 368 - 22 hours harsh tested before rust. Our product is chromed on plateable quality tubing after all welding is completed.

Glide System: Glide attachment will be a standard internal gripping spring steel umbrella at least 5/8" diameter or larger. The glide will have a ferrule. Glide casing and ferrule shall be constructed of durable case hardened steel; no plastic. The glide will be of full swivel design, silent and firm fitting for positive attachment and retention. All glides must make full level contact with the floor and the maximum swivel angle of the glide shall not be violated. Incorporating our exclusive glide button system available in either nylon, neoprene, steel, or wool felt bottom. Pick the right base for the floor surface. Snap on a new base for surface change or wear replacement.



Book box: Lift-Lid: 22-1/4" x 16" x 5" deep, 20-gauge, one piece, seamless, deep drawn

steel box. Embossed shelf and stamped pencil tray. Top attached by full length piano hinge riveted to box and two silent friction hinges which control top. Book box is riveted to frame at five points.

Seat & Back: Only 5/8" thick posture contoured solid molded thermo-set plastic with smooth molded edges and permanent color throughout thickness shall be used. Seat size is at least 16" wide x 15-1/2" deep. Back size is at least 14" wide x 6-1/2" high on all chair heights. Both seat and back must be attached through punched holes on a contoured tubular frame using self-tapping screws into four uniformly drilled holes.

Seat & Back Attachments: Both seat and back are attached through punched holes in tubular frame using self-tapping screws into four uniformly drilled holes. Seats and backs shall be attached in four places each without the use of spacers, washers or noise reducers (attachment systems that create any noise without these devices are not acceptable).

Top: Solid molded thermo-set plastic (18" x 24" x 5/8") with smooth molded edges, pencil groove and homogeneous color. Top is attached using self-tapping screws into seven uniformly drilled holes.

- Warranty:**
- Limited Lifetime Frame Warranty
 - Ten Year Comprehensive Warranty

- Models:**
- 965 15-1/2" Seat Height
 - 967 17-1/2" Seat Height

