

3524 - 3530 EUROFLEX SIT/STAND CHAIR



F E A T U R E S

- Collaborative four-way seat design ● Distinctive, generously sculpted, dual-textured shell ● Responsive, active, posture correct back ● High-Impact, bluish resistant, anti-static, one-piece polypropylene shell ● Waterfall front for enhanced circulation ● Built-in handle in seat back ● Chair inverts on desk for floor maintenance ● Innovative mobility wings in seat provide more surface and allow grips for movement ● 1-1/8" 16 gauge legs ● Long-ferrule inside holding nylon glides ● Exclusive dual stacking system ● 13 gauge seat brackets ● Superior extra-long welds ● Concealed Rivets ● Glides make full contact with floor due to proper vertical load distribution ● Lifetime Frame Warranty ● USA Made and USA sourced raw materials ● Rainbow of shell



Exclusive Glide System

Choose the glide base you need for your floor surface.
When glide needs replacement, snap-lock on a new base.
Nylon, Neoprene, Steel, Wool Felt



USACAPITOL, 209 E GROVE ROAD, BELTON, TX 76513

800-460-1272

WWW.USACAPITOL.COM



Very well made in the USA.



H I G H L I G H T S

- Premium Quality Materials
- Modern Collaborative Design
- Dual Stacking System
- 16 Gauge Legs
- 13 Gauge Under Structure
- Lifetime Frame Warranty
- 2 Seat Heights
- 22 Standard Shell Colors
- Blushing / Antistat Additive

Euroflex™ Chair Specifications

Frame: 24" or 30" unit: 1-1/8" diameter, 16-gauge legs. All units are welded together with two seat brackets of 13-gauge die-formed steel, integrally tying all tube parts for maximum structural integrity. Frame is hard nickel chrome plated after all welding is complete.

Standard Chrome Finish: Chrome is comprised of metal layers (Nickel & Chromium) electrostatically bonded to metal. Our standard is 4-6 mills (25%-50% more than our competitors) of Nickel. Hard-Chrome will not scratch. CASS test per ASTM B 368 - 22 hours harsh tested before rust. Our product is chromed on plateable quality tubing after all welding is completed.

Glide System: Glide attachment will be a standard internal gripping spring steel umbrella at least 5/8" diameter or larger. The glide will have a ferrule. Glide casing and ferrule shall be constructed of durable case hardened steel; no plastic. The glide will be of full swivel design, silent and firm fitting for positive attachment and retention. All glides must make full level contact with the floor and the maximum swivel angle of the glide shall not be violated. Incorporating our exclusive glide button system available in either nylon, neoprene, steel, or wool felt bottom. Pick the right base for the floor surface. Snap on a new base for surface change or wear replacement.



Euroflex™ Shell: Generously sculpted one-piece shell is injection molded from proprietary high impact, bluish resistant polypropylene plastic with an antistatic additive. Collaborative seat design can be comfortably sat in all four directions. Dual textured surface is etched to provide a non-slip surface while assisting in maintaining like-new appearance. Responsive, active, back encourages proper task position as well as ventilation. Seat back incorporates handle for movement. Innovative design and rib pattern transfers weight to the frame while adding rhythm and movement. Mobility wings in seat provide more surface and grips for movement. Shell design allows inverted stacking on desk for floor maintenance. The shell is attached to frame with four concealed machine rivets. Waterfall front for enhanced circulation. Exclusive dual-stacking design.

Warranty:

- Limited lifetime frame warranty
- Ten Year Comprehensive Warranty

Models:

- 3524*24"
- 3530*30"

Shell Size: 18.5" wide x 15.5" deep

Shell Colors: (Pictured in order at bottom of page) Available in standard Black, Navy, Wine, Taupe, Hunter, Mint, Green Apple, Peacock, Cardinal, Sky, Sunflower, Sunset, Slate, Copper, Orchid, Violet, Java, Burnt Orange, Graphite, Kiwi, Turquoise, Grape.

FRAME OPTIONS



SEAT PAD - FABRIC OPTIONS

