

470DBL APTITUDE TWO STUDENT OPEN FRONT



H I G H L I G H T S



- Premium Quality
- Embossed Pencil Tray
- 18 Gauge Legs & Book box
- Unitized Frame Structure

- Lifetime Frame Warranty
- Rolled Reinforced Front Edge
- Multiple Top Color Options
- Textured Powdercoat

Aptitude™ 470DBL Two-Student Open Front Desk Specifications

Frame/Bookbox: Self-standing with built-in 18-gauge steel book box. 1-1/4" diameter, 18-gauge leg uppers form the corners of the book compartment for added strength and ease of cleaning. The leg uppers are mig welded to the book box and a 5/8" U-Brace is welded to all four legs. 5-1/4"x42"x16-1/2" extra-large divided book box with safety edge and stamped pencil trays. Minimum 14" of total weld. Frame is texture powder-coated after all welding is complete. Textured Powdercoat to hide fingerprints and greater wear resistance.

for positive attachment and retention. All glides must make full level contact with the floor and the maximum swivel angle of the glide shall not be violated. Incorporating our exclusive glide button system available in either nylon, neophrene, steel, or wool felt bottom. Pick the right base for the floor surface. Snap on a new base for surface change or wear replacement.



Frame/Book box Colors: Available in standard Textured Black and Textured Titanium. Optional Textured Navy and Textured Sand. Textured powdercoating hides fingerprints and improves surface wear life.

Laminate Top: Three-ply construction. 24"x48"x1-1/8" High pressure laminate and backer are 'fused' to the wood core base using a glue web formulation that is clean, environmentally safe, extremely consistent. 3/8" bull-nosed bumper edging that is mechanically fastened every 6 to 8 inches. Top is attached using self-tapping screws into fourteen uniformly drilled holes. No pencil groove.

Inserts: 1.110" diameter, 16-gauge nickel/chrome plated tubing with punched holes to receive adjusting screws. Leg adjustment uses self-tapping locking screws which pass completely through both upper leg and lower insert. Dual-bolt attachment at 1" increments.

Warranty:

- Limited lifetime frame warranty
- Ten Year Comprehensive

Chrome Inserts: .86" diameter, nickel/chrome plated 16ga tubing with punched holes to receive adjusting screws. Leg adjustment uses self-tapping locking screws which pass completely through both upper leg and lower insert. Chrome is comprised of metal layers (Nickel & Chromium) electrostatically bonded to metal. Our standard is 4-6 mills (25%-50% more than our competitors) of Nickel--it will not scratch.

Warranty:

- Limited lifetime frame warranty
- Ten Year Comprehensive Warranty

Models:

- 470DBL24SE•22-1/4" - 30-1/4" Adjustable at 1" Increments, Laminate top with spray edge


Glide System: Glide attachment will be a standard internal gripping spring steel umbrella at least 5/8" diameter or larger. The glide will have a ferrule. Glide casing and ferrule shall be constructed of durable case hardened steel; no plastic. The glide will be of full swivel design, silent and firm fitting



Bumper Mold Edge Available On This Item Upon Request.

PLEASE NOTE:
Desk Orders
Meeting Volume Quantities
ALWAYS Have the Option of
Choosing ANY Standard
Formica or WilsonArt Laminate at
NO ADDITIONAL UPCHARGE

Standard
Powdercoated
Frame Colors:



STANDARD LAMINATE OPTIONS - SEE PAGE 88.
SPRAY EDGE - STANDARD BLACK OR GRAPHITE.

OPTIONAL SPRAY EDGE COLORS NO UPCHARGE ON SAME COLORS 50 OR MORE
- SEE PAGE 88 FOR OPTIONS